

1NZ-FE EMISSION CONTROL

SERVICE DATA

Vacuum switching valve (Purge VSV)	Standard resistance		23 to 26 Ω at 20°C (68°F)
Heated oxygen sensor (for Bank 1 Sensor 1)	Standard resistance	1 (HT) - 2 (+B)	11 to 16 Ω at 20°C (68°F)
		1 (HT) - 4 (E1)	10 k Ω or higher
Heated oxygen sensor (for Bank 1 Sensor 2)	Standard resistance	1 (HT) - 2 (+B)	11 to 16 Ω at 20°C (68°F)
		1 (HT) - 4 (E1)	10 k Ω or higher

SS

TORQUE SPECIFICATIONS

Part Tightened	N*m	kgf*cm	ft.*lbf
Charcoal canister x Body	19	194	14
Ventilation valve x Cylinder head cover	27	275	20
Heated oxygen sensor (for bank 1 sensor 1) x Front exhaust pipe : for use with SST	44	449	32
Heated oxygen sensor (for bank 1 sensor 1) x Front exhaust pipe : for use without SST	40	408	30
Heated oxygen sensor (for bank 1 sensor 1) x Front exhaust pipe : for use with SST	44	449	32
Heated oxygen sensor (for bank 1 sensor 1) x Front exhaust pipe : for use without SST	40	408	30

SS