


**DTC****B1185/57****Short in Front Passenger Side Squib 2nd Step Circuit****DESCRIPTION**

The front passenger side squib (2nd step) circuit consists of the center airbag sensor assembly and the front passenger airbag assembly.

This circuit instructs the SRS to deploy when deployment conditions are met.

DTC B1185/57 is recorded when a short circuit is detected in the front passenger side squib (2nd step) circuit.


DTC No.	DTC Detection Condition	Trouble Area
B1185/57	<ul style="list-style-type: none"> <li>Short circuit between P2+ wire harness and P2- wire harness of front passenger side squib (2nd step)</li> <li>Front passenger side squib (2nd step) malfunction</li> <li>Center airbag sensor assembly</li> </ul>	<ul style="list-style-type: none"> <li>Front passenger airbag assembly (front passenger side squib, 2nd step)</li> <li>Center airbag sensor assembly</li> <li>Instrument panel wire</li> </ul>

**WIRING DIAGRAM**

1

CHECK INSTRUMENT PANEL WIRE (FRONT PASSENGER SIDE SQUIB CIRCUIT (2ND STEP))

RS



OK

- (a) Turn the ignition switch to the LOCK position.
- (b) Disconnect the negative (-) terminal cable from the battery, and wait for at least 90 seconds.
- (c) Disconnect the connectors from the center airbag sensor assembly and the front passenger airbag assembly.
- (d) Release the activation prevention mechanism built into connector "B" (see page RS-12).
- (e) Measure the resistance according to the value(s) in the table below.

Standard resistance

Tester Connection (Connector "C")	Specified Condition
A12-3 (P2+) - A12-4 (P2-)	1 MΩ or higher


NG

REPAIR OR REPLACE INSTRUMENT PANEL WIRE

2

CHECK CENTER AIRBAG SENSOR ASSEMBLY

- (a) Connect the connector to the center airbag sensor assembly.
- (b) Connect the negative (-) terminal cable to the battery, and wait for at least 2 seconds.
- (c) Turn the ignition switch to the ON position, and wait for at least 60 seconds.
- (d) Clear the stored DTCs in the memory (see page RS-21).
- (e) Turn the ignition switch to the LOCK position.
- (f) Turn the ignition switch to the ON position, and wait for at least 60 seconds.



(g) Check for the DTCs (see page [RS-21](#)).

**OK:**

**DTC B1185/57 is not output.**

**HINT:**

Codes other than code B1185/57 may be output at this time, but they are not related to this check.

**NG**

**REPLACE CENTER AIRBAG SENSOR ASSEMBLY**

**RS**


**OK**

**3**

**CHECK FRONT PASSENGER AIRBAG ASSEMBLY (FRONT PASSENGER SIDE SQUIB, 2ND STEP)**

- Turn the ignition switch to the LOCK position.
- Disconnect the negative (-) terminal cable from the battery, and wait for at least 90 seconds.
- Connect the connector to the front passenger airbag assembly.
- Connect the negative (-) terminal cable to the battery, and wait for at least 2 seconds.
- Turn the ignition switch to the ON position, and wait for at least 60 seconds.
- Clear the stored DTCs in the memory (see page [RS-21](#)).
- Turn the ignition switch to the LOCK position.
- Turn the ignition switch to the ON position, and wait for at least 60 seconds.

RS



- (i) Check for the DTCs (see page [RS-21](#)).

**OK:**

**DTC B1185/57 is not output.**

**HINT:**

Codes other than code B1185/57 may be output at this time, but they are not related to this check.

**NG**

**REPLACE FRONT PASSENGER AIRBAG ASSEMBLY**

**OK**

**PROBLEM SYMPTOMS SIMULATION**